



All instructions refer to the seated position

The Denbigh D02 chair has been designed to offer excellent comfort with a breathable membrane back. These features help promote good user posture and will reduce fatigue during the working day.

1. The lever located front right below the seat, operates the seat height adjustment. Twisting the lever up whilst taking weight off the chair seat allows the seat to rise. The sitting position can then be fixed by simply returning the lever to its start position. Conversely twisting the lever up whilst maintaining weight on the seat allows the seat to fall.
2. The winding handle on the same spindle as the seat height lever operates the reclining action tension, allowing the user to adjust the chair to suit their body weight. Winding clockwise increases the tension and anti-clockwise reduces it. The handle can be pulled out for ease of use.
3. The winding handle on the left side, operates the chair reclining action. This action is synchronised which means that the back angle increases more quickly than the seat angle when reclining backwards. To operate simply twist the handle and lean back. There should be a little resistance to your body weight (see instruction 2). The chair can now be used in this floating mode or locked in the desired position by twisting the handle back. The mechanism also has an 'anti-shock' feature which prevents the back springing forward when the wheel is operated. To bring the chair forward from a locked position, twist the wheel, recline backwards a little and then bring your weight forwards - the back will come with you.
4. The chair is fitted with a height adjustable lumbar support, which is best adjusted from the seating position by placing both arms behind the back of the chair, and sliding the lumbar support pad up and down on the ratchet mechanism to the desired most comfortable and supporting position.
5. Seat Slide (Optional Extra). There is a separate shaped lever on the left-hand side on the same spindle as the reclining action handle described in 3 above. Raising the lever allows the seat slide to be pulled out or to release the mechanism.
6. The height adjustable arms are height adjustable by using the button on the outside of the arm. Simply push the button in to lift the arm and release the button to lock in position.
7. The chair is designed to accommodate users weighing up to 150kg.
8. All chairs are built to comply with BS5459 (1990) Part 2.